


AD-A112 616 CALIFORNIA UNIV LOS ANGELES INTEGRATED ELECTROMAGNET--ETC F/6 20/14
MICROSTRIP DIPOLES ON CYLINDRICAL STRUCTURES.(U)
DEC 81 N S ALEXOPOULOS, P L USLENGHI DAA629-79-C-0050
UNCLASSIFIED UCLA-ENG-82-14 ARO-15965.12-EL NL


1 of 1
2000





ARO 15965.12-EL

(12)



AD A112616

Integrated Electromagnetics Laboratory Report No. 5
UCLA Report No. ENG 82-14
January 19, 1982

"MICROSTRIP DIPOLES ON CYLINDRICAL STRUCTURES"


by

N. G. Alexopoulos, P.L.E. Uslenghi and
N.K. Usunoglu

Sponsored by:

U.S. Army Contract DAAG 29-79-C-0050

DTIC FILE COPY



This document has been approved
for public release and sales in
distribution is unlimited.

82 08 24 026

UCLA - SCHOOL OF ENGINEERING AND APPLIED SCIENCE

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. <i>AD-A112 616</i>	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Microstrip Dipoles on Cylindrical Structures		5. TYPE OF REPORT & PERIOD COVERED Technical Laboratory Report
7. AUTHOR(s) N. G. Alexopoulos, P.L.E. Uslenghi and N.K. Uzunoglu		6. PERFORMING ORG. REPORT NUMBER Integrated Electromagnetics Lab. Report No. 5
9. PERFORMING ORGANIZATION NAME AND ADDRESS Electrical Engineering Department UCLA Los Angeles, CA 90024		8. CONTRACT OR GRANT NUMBER(s) DAAG29-79-C-0050
11. CONTROLLING OFFICE NAME AND ADDRESS Dr. James Mink ARO - P 4800-C-81		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Army Research Office Research Triangle Park North Carolina		12. REPORT DATE December 1981
		13. NUMBER OF PAGES 20
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Reproduction in whole or in part is permitted for any purpose of the U.S. Government.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES THE VIEW, OPINIONS, AND/OR FINDINGS CONTAINED IN THIS REPORT ARE THOSE OF THE AUTHOR(S) AND SHOULD NOT BE CONSTRUED AS AN OFFICIAL DEPARTMENT OF THE ARMY POSITION, POLICY, OR DE- CISION, UNLESS SO DESIGNATED BY OTHER DOCUMENTATION.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Microstrip Dipoles Cylindrical Structures		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) An electric dipole tangent to the outer surface of a dielectric layer which coats a metallic cylinder is considered. Exact expressions are obtained for the electromagnetic field produced by the dipole, both inside the coating layer and in the surrounding free space. Asymptotic results are derived for a cylinder whose diameter is large compared to the wavelength. Arrays of elem- entary dipoles are discussed.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF 014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Microstrip Dipoles on Cylindrical Structures (*)

N. G. Alexopoulos
Electrical Engineering Department
University of California at Los Angeles
Los Angeles, CA 90024

P. L. E. Uslenghi
Department of Information Engineering
University of Illinois at Chicago Circle
Chicago, IL 60680

N. K. Uzunoglu
Department of Electrical Engineering
National Technical University of Athens
Athens TT-147, Greece

Accession For	
NTIS GNA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification on <i>form 50</i>	
By	
Dist	Section/
Availability Codes	
Dist	Avail and/or Special
A	

(*) Research supported by U. S. Army Research contract DAAG29-79-C-0050

1. Abstract

An electric dipole tangent to the outer surface of a dielectric layer which coats a metallic cylinder is considered. Exact expressions are obtained for the electromagnetic field produced by the dipole, both inside the coating layer and in the surrounding free space. Asymptotic results are derived for a cylinder whose diameter is large compared to the wavelength. Arrays of elementary dipoles are discussed.

2. Introduction

Microstrip antennas and arrays have received increasing attention in the scientific literature during the past few years, largely as a consequence of advances in printed circuit technology. The state of the art, in both theoretical and experimental studies, is summarized in the book by Bahl and Bhartia [1] and in the special issue [2], which contains two exhaustive review papers on these subjects [3,4]. The geometries of microstrip antennas are not conducive to easy analytical treatment; for example, rectangular and triangular microstrip patch antennas may be studied by combining function-theoretic methods with ray-tracing techniques [5,6,7]. Therefore numerical treatments, based e.g. on the moment method [8], have been extensively adapted, especially for computation of input impedance and mutual impedance [9,10].

Although most studies carried out so far have dealt with planar substrates, from a practical viewpoint it is very important to consider the case of printed antennas and arrays on curved surfaces, especially on portions of cylinders, cones or spheres. Together with a companion work on spherical structures [11], this paper presents a detailed study of dipoles on a dielectric-coated cylindrical structure. The exact field produced by an electric dipole tangent to the outer surface of

the coating layer is given in Section 3; the results are specialized to the radiated far field and to the surface field. An asymptotic analysis for the radiated equatorial field due to a longitudinal dipole is given in Section 4, for a thin substrate and a cylinder whose diameter is large compared to the wavelength. Preliminary results for arrays of such longitudinal dipoles are presented in Section 5. The time-dependence factor $\exp(-i\omega t)$ is omitted throughout.

3. Exact Solution

Consider an infinitely long, perfectly conducting cylinder of radius $\rho = a$ coated by a uniform layer of constant thickness $D = b - a$, permittivity $\epsilon\epsilon_0$ and permeability μ_0 , and immersed in free space (see fig. 1).

Let us introduce a cylindrical coordinate system ρ, ϕ, z with the z axis on the axis of the cylinder. The primary source is an electric dipole located at $\underline{r}_0 \equiv (\rho_0, \phi_0, z_0)$ where $\rho_0 \geq b$, and whose electric dipole moment is

$$\underline{p} = \frac{4\pi\epsilon_0}{k} \hat{c}, \quad (1)$$

where \hat{c} is a unit vector and $k = \omega\sqrt{\epsilon_0\mu_0}$ is the free-space wave-number. The source strength of Eq. (1) corresponds to an incident (or primary) electric Hertz vector

$$\underline{\Pi}_e = \frac{e^{ikR}}{kR} \hat{c}, \quad R = |\underline{r} - \underline{r}_0|, \quad (2)$$

where $\underline{r} \equiv (\rho, \phi, z)$ is the position of the observation point. It should be noted that with the primary source normalized as in Eqs. (1,2), the electric dyadic Green's function has dimensions of m^{-1} , whereas the

field is measured in m^{-2} .

The total (incident plus scattered) electric field is given by:

$$\begin{aligned}\underline{E}(\underline{r}) &= 4\pi k \underline{G}_e^{(I)}(\underline{r}; \underline{r}_0) \cdot \hat{c}, \quad a \leq \rho \leq b \\ &= 4\pi k \underline{G}_e^{(II)}(\underline{r}; \underline{r}_0) \cdot \hat{c}, \quad \rho \geq b.\end{aligned}\quad (3)$$

The electric dyadic Green's functions $\underline{G}_e^{(I)}$ in the coating layer and $\underline{G}_e^{(II)}$ in the surrounding medium may be obtained by the method described by Tai [12], as amended in [13,14]. It should be noted that disagreements on the singular term which appears in Eq. (6) below (see e.g. [15]) are of no relevance here, because the $\hat{\rho}\hat{\rho}$ term does not contribute to the field generated by a dipole tangent to the cylinder (i.e., $\hat{c} \cdot \hat{\rho} = 0$).

After imposing the boundary conditions at the perfectly conducting surface $\rho = a$ and across the dielectric interface $\rho = b$, as well as the radiation condition at $\rho \rightarrow \infty$, it is found that:

$$\begin{aligned}\underline{G}_e^{(I)}(\underline{r}; \underline{r}_0) &= \frac{1}{8\pi} \int_{-\infty}^{\infty} du \sum_{n=0}^{\infty} \frac{\tau_n}{\eta^2} \sum_{e,o} \left(\left[A_n \left[\frac{M_{en,\xi}^{(1)}(u, \underline{r})}{\delta_{en,\xi}^{(1)}} + \alpha \frac{M_{en,\xi}^{(3)}(u, \underline{r})}{\delta_{en,\xi}^{(3)}} \right] + \right. \right. \\ &\quad \left. \left. + C_n \left[\frac{N_{en,\xi}^{(1)}(u, \underline{r})}{\delta_{en,\xi}^{(1)}} + \beta \frac{N_{en,\xi}^{(3)}(u, \underline{r})}{\delta_{en,\xi}^{(3)}} \right] \right] \frac{M_{en,\eta}^{(3)}(-u, \underline{r}_0)}{\delta_{en,\eta}^{(3)}} + \right. \\ &\quad \left. + \left[B_n \left[\frac{N_{en,\xi}^{(1)}(u, \underline{r})}{\delta_{en,\xi}^{(1)}} + \beta \frac{N_{en,\xi}^{(3)}(u, \underline{r})}{\delta_{en,\xi}^{(3)}} \right] + \right. \right. \\ &\quad \left. \left. + D_n \left[\frac{M_{en,\xi}^{(1)}(u, \underline{r})}{\delta_{en,\xi}^{(1)}} + \alpha \frac{M_{en,\xi}^{(3)}(u, \underline{r})}{\delta_{en,\xi}^{(3)}} \right] \right] \frac{N_{en,\eta}^{(3)}(-u, \underline{r}_0)}{\delta_{en,\eta}^{(3)}} \right),\end{aligned}\quad (4)$$

$$\underline{G}_e^{(II)}(\underline{r}; \underline{r}_0) = \underline{G}_{eo}(\underline{r}; \underline{r}_0) + \underline{G}_{es}(\underline{r}; \underline{r}_0), \quad (5)$$

$$\underline{G}_{eo}(\underline{r}; \underline{r}_0) = -k^{-2} \hat{\rho} \hat{\rho} \delta(\underline{r} - \underline{r}_0) + \underline{G}_{eo}^{(<)}(\underline{r}; \underline{r}_0), \quad (\rho \geq \rho_0), \quad (6)$$

$$\begin{aligned}\underline{G}_{eo}^{(>)}(\underline{r}; \underline{r}_0) &= \frac{1}{8\pi} \int_{-\infty}^{\infty} du \sum_{n=0}^{\infty} \frac{\tau_n}{\eta^2} \sum_{e,o} \left[\frac{M_{en,\eta}^{(3)}(u, \underline{r})}{\delta_{en,\eta}^{(3)}} \frac{M_{en,\eta}^{(1)}(-u, \underline{r}_0)}{\delta_{en,\eta}^{(1)}} + \right. \\ &\quad \left. + \frac{N_{en,\eta}^{(3)}(u, \underline{r})}{\delta_{en,\eta}^{(3)}} \frac{N_{en,\eta}^{(1)}(-u, \underline{r}_0)}{\delta_{en,\eta}^{(1)}} \right], \quad (\rho > \rho_0), \quad (7)\end{aligned}$$

$$\begin{aligned} G_{eo}^{(<)}(\underline{r}; \underline{r}_0) = \frac{1}{8\pi} \int_{-\infty}^{\infty} du \sum_{n=0}^{\infty} \frac{\tau_n}{n^2} \sum_{e,o} \left[\frac{M_{en,\eta}^{(1)}(u, \underline{r})}{\rho} \frac{M_{en,\eta}^{(3)}(-u, \underline{r}_0)}{\rho} + \right. \\ \left. + \frac{N_{en,\eta}^{(1)}(u, \underline{r})}{\rho} \frac{N_{en,\eta}^{(3)}(-u, \underline{r}_0)}{\rho} \right], \quad (\rho < \rho_0), \end{aligned} \quad (8)$$

$$\begin{aligned} G_{es}(\underline{r}; \underline{r}_0) = \frac{1}{8\pi} \int_{-\infty}^{\infty} du \sum_{n=0}^{\infty} \frac{\tau_n}{n^2} \sum_{e,o} \left\{ \left[a_{n-\frac{o}{e}} \frac{M_{en,\eta}^{(3)}(u, \underline{r})}{\rho} + \right. \right. \\ \left. \left. + c_{n-\frac{o}{e}} \frac{N_{en,\eta}^{(3)}(u, \underline{r})}{\rho} \right] \frac{M_{en,\eta}^{(3)}(-u, \underline{r}_0)}{\rho} + \left[b_{n-\frac{o}{e}} \frac{M_{en,\eta}^{(3)}(u, \underline{r})}{\rho} + \right. \right. \\ \left. \left. + c_{n-\frac{o}{e}} \frac{M_{en,\eta}^{(3)}(u, \underline{r})}{\rho} \right] \frac{N_{en,\eta}^{(3)}(-u, \underline{r}_0)}{\rho} \right\}, \end{aligned} \quad (9)$$

where

$$\begin{aligned} \frac{M_{en,\eta}^{(j)}(u, \underline{r})}{\rho} = v_x \left[\frac{Z_n^{(j)}(\eta\rho) \cos(n\phi) e^{iuz} \hat{z}}{\sin} \right] = \\ = e^{iuz} \left[\mp \frac{n}{\rho} \frac{Z_n^{(j)}(\eta\rho) \sin(n\phi) \hat{\rho}}{\cos} - \frac{\partial}{\partial \rho} \frac{Z_n^{(j)}(\eta\rho) \cos(n\phi) \hat{\phi}}{\sin} \right], \end{aligned} \quad (10)$$

$$\begin{aligned} \frac{N_{en,\eta}^{(j)}(u, \underline{r})}{\rho} = \frac{1}{\sqrt{u^2 + \eta^2}} v_x \frac{M_{en,\eta}^{(j)}(u, \underline{r})}{\rho} = \\ = \frac{e^{iuz}}{\sqrt{u^2 + \eta^2}} \left[iu \frac{\partial}{\partial \rho} \frac{Z_n^{(j)}(\eta\rho) \cos(n\phi) \hat{\rho}}{\sin} + \frac{i u \rho}{\rho} \frac{Z_n^{(j)}(\eta\rho) \sin(n\phi) \hat{\phi}}{\cos} + \right. \\ \left. + \eta^2 \frac{Z_n^{(j)}(\eta\rho) \cos(n\phi) \hat{z}}{\sin} \right], \end{aligned} \quad (11)$$

$$\eta = \sqrt{k^2 - u^2}, \quad \xi = \sqrt{k_1^2 - u^2}, \quad k_1 = \epsilon k = N^2 k, \quad (12)$$

$j = 1$ or 3 , $Z_n^{(1)}(x) = J_n(x)$ and $Z_n^{(3)}(x) = H_n^{(1)}(x)$ are the Bessel function and the Hankel function of the first kind, $\delta(\underline{r} - \underline{r}_0)$ is the three-dimensional Dirac delta-function, $\tau_0 = 1$ and $\tau_n > 0 = 2$, and

the integral path along the real u -axis passes below the points $u = k$, $u = k_1$ and above the points $u = -k$, $u = -k_1$ (see fig. 2).

The various coefficients which appear in Eqs. (4) and (9) are given by (the prime means derivative with respect to the argument of the primed function):

$$\alpha_n = -\frac{J'_n(\xi a)}{H_n^{(1)}(\xi a)}, \quad \beta_n = -\frac{J_n(\xi a)}{H_n^{(1)}(\xi a)} \quad (13)$$

$$A_n = N \frac{\Gamma_{n\beta}}{\Gamma_{n\alpha}} B_n = \frac{2i\Gamma_{n\beta}}{\pi b \delta_n H_n^{(1)}(\eta b)}, \quad (14)$$

$$C_n = N \frac{\gamma_{n\alpha}}{\gamma_{n\beta}} D_n = \frac{2n\gamma_{n\alpha}}{\pi k_1 b^2 \delta_n H_n^{(1)}(\eta b)} \left(1 - \frac{\xi^2}{\eta^2}\right), \quad (15)$$

$$a_n = -\frac{J_n(\eta b)}{H_n^{(1)}(\eta b)} + \frac{\xi^2 \gamma_{n\alpha}}{\eta^2 H_n^{(1)}(\eta b)} A_n, \quad (16)$$

$$b_n = -\frac{J_n(\eta b)}{H_n^{(1)}(\eta b)} + \frac{\xi^2 \gamma_{n\beta}}{N \eta^2 H_n^{(1)}(\eta b)} B_n, \quad (17)$$

$$c_n = \frac{\xi^2 \gamma_{n\beta}}{N \eta^2 H_n^{(1)}(\eta b)} C_n, \quad (18)$$

where

$$\gamma_{n\alpha} = J_n(\xi b) + \alpha_n H_n^{(1)}(\xi b), \quad \gamma_{n\beta} = J_n(\xi b) + \beta_n H_n^{(1)}(\xi b), \quad (19)$$

$$\Gamma_{n\alpha} = -\frac{\partial \gamma_{n\alpha}}{\partial b} + \frac{\xi^2}{2} \gamma_{n\alpha} \frac{\partial}{\partial b} \ln H_n^{(1)}(\eta b), \quad (20)$$

$$\Gamma_{n\beta} = -\frac{\partial \gamma_{n\beta}}{\partial b} + \frac{\xi^2}{2} \gamma_{n\beta} \frac{\partial}{\partial b} \ln H_n^{(1)}(\eta b), \quad (21)$$

$$\delta_n = \Gamma_{na} \Gamma_{n\beta} - \left(\frac{nu}{k_1 b} \right)^2 \left(1 - \frac{\xi^2}{\eta^2} \right)^2 \gamma_{na} \gamma_{n\beta}. \quad (22)$$

The above formulas can be considerably simplified in particular case. Consider, for example, an axially-oriented dipole ($\hat{c} = \hat{z}$) located on the substrate ($\rho_0 = b$); the total electric field on the substrate and in the equatorial plane $z = z_0$ is:

$$[\underline{E}]_{\substack{\rho=\rho_0=b \\ z=z_0 \\ \hat{c}=\hat{z}^0}} = \hat{z} \frac{-2}{\pi \epsilon k^2 b} \sum_{n=0}^{\infty} \tau_n \cos n(\phi - \phi_0) \int_0^{\infty} du \gamma_{n\beta} \Gamma_{na} \xi^2 \delta_n^{-1}. \quad (23)$$

In the more general case when the dipole at $\underline{r}_0 = (b, \phi_0, z_0)$ is tangent to the substrate but not necessarily axially oriented, i.e.

$$\hat{c} = \hat{c} \cdot \hat{\phi}_0 \hat{\phi}_0 + \hat{c} \cdot \hat{z} \hat{z}, \quad \hat{c} \cdot \hat{\rho}_0 = 0, \quad (24)$$

then the electric field at any point \underline{r} in free space is:

$$\underline{E}(\underline{r}) = \underline{E}_{\perp} \hat{c} \cdot \hat{\phi}_0 + \underline{E}_{\parallel} \hat{c} \cdot \hat{z}, \quad (25)$$

where

$$\begin{aligned} \underline{E}_{\perp} = & \frac{1}{\pi k b} \int_{-\infty}^{\infty} du k^2 \eta^{-2} e^{-iuz_0} \sum_{n=0}^{\infty} \frac{\tau_n}{H_n^{(1)}(\eta b)} \sum_{e,o} \cos(n\phi_0) \cdot \\ & \cdot \left\{ \left[-1 + \frac{\xi^2 \gamma_{na} \Gamma_{n\beta} H_n^{(1)'}(\eta b)}{\eta \delta_n H_n^{(1)}(\eta b)} - \frac{n^2 u^2 \xi^2 \gamma_{na} \gamma_{n\beta}}{\eta^2 k_1^2 b^2 \delta_n} \left(\frac{\xi^2}{\eta^2} - 1 \right) \right] \frac{M_{on,n}^{(3)}(u, \underline{r})}{\epsilon} \pm \right. \\ & \left. \pm \frac{i n u \gamma_{n\beta} \xi^2}{\epsilon k b \delta_n \eta} \left[\eta^{-1} \Gamma_{na} - \gamma_{na} \left(\frac{\xi^2}{\eta^2} - 1 \right) \frac{H_n^{(1)'}(\eta b)}{H_n^{(1)}(\eta b)} \right] \frac{N_{on,n}^{(3)}(u, \underline{r})}{\epsilon} \right\}, \quad (26) \\ \underline{E}_{\parallel} = & \frac{1}{\pi \epsilon b} \int_{-\infty}^{\infty} du \xi^2 \eta^{-2} e^{-iuz_0} \sum_{n=0}^{\infty} \frac{\tau_n \gamma_{n\beta}}{\delta_n H_n^{(1)}(\eta b)} \sum_{e,o} \cos(n\phi_0) \cdot \end{aligned}$$

$$\cdot \left[-\gamma_{na} \frac{N^{(3)}_{0n,n}(u, \underline{r})}{\delta_{0n,n}} \pm \frac{i n u}{k b} \left(\frac{\epsilon^2}{\eta^2} - 1 \right) \gamma_{na} \frac{N^{(3)}_{0n,n}(u, \underline{r})}{\delta_{0n,n}} \right]. \quad (27)$$

In the far field ($\rho \rightarrow \infty$), the integrals in Eqs. (26-27) may be asymptotically evaluated by the method of stationary phase, the stationary point being at $u = k \cos \theta$, where $\theta = \arccos(z/r)$ is the usual polar angle in spherical coordinates. If we write the radiated field as

$$\left. \begin{aligned} \underline{E}_{||}(\underline{r}) &= -k^2 \frac{e^{ikr}}{kr} \underline{S}_{||}(\hat{r}), \\ \underline{E}_{\perp}(\underline{r}) &= -k^2 \frac{e^{ikr}}{kr} \underline{S}_{\perp}(\hat{r}), \end{aligned} \right\} \quad (\rho \rightarrow \infty) \quad (28)$$

then the dimensionless far-field coefficients $\underline{S}_{||}$ and \underline{S}_{\perp} are

$$\begin{aligned} \underline{S}_{||}(\hat{r}) &= S_{||\theta} \hat{\theta} + S_{||\phi} \hat{\phi} \\ &= \frac{2i}{\pi \zeta} \left(1 - \frac{\cos^2 \theta}{\epsilon} \right) e^{-ikz_0 \cos \theta} (A_{\theta} \hat{\theta} + A_{\phi} \hat{\phi}), \end{aligned} \quad (29)$$

$$\begin{aligned} \underline{S}_{\perp}(\hat{r}) &= S_{\perp\theta} \hat{\theta} + S_{\perp\phi} \hat{\phi} \\ &= \frac{2}{\pi \zeta} e^{-ikz_0 \cos \theta} (B_{\theta} \hat{\theta} + B_{\phi} \hat{\phi}), \end{aligned} \quad (30)$$

where

$$\zeta = k b \sin \theta, \quad (31)$$

$$A_{\theta} = \sum_{n=0}^{\infty} \gamma_n (-1)^n \frac{k \tilde{\gamma}_{n\theta} \tilde{\gamma}_{na}}{\delta_{n,n}^{(1)}(\zeta)} \cos n(\phi - \phi_0), \quad (32)$$

$$A_{\phi} = (\epsilon - 1) \frac{2 \cot \theta}{\zeta} \sum_{n=1}^{\infty} (-1)^n \frac{k^2 \tilde{\gamma}_{n\theta} \tilde{\gamma}_{n\phi}}{\delta_{n,n}^{(1)}(\zeta)} \sin n(\phi - \phi_0), \quad (33)$$

$$B_{\theta} = \left(1 - \frac{\cos^2 \theta}{\epsilon}\right) \frac{2 \cot \theta}{\zeta} \sum_{n=1}^{\infty} (-1)^n \frac{k^2 \tilde{\gamma}_{n\beta}}{\tilde{\delta}_n H_n^{(1)}(\zeta)} \left[k^{-1} \tilde{r}_{n\alpha} - \frac{\epsilon - 1}{\sin \theta} \tilde{\gamma}_{n\alpha} \frac{H_n^{(1)'}(\zeta)}{H_n^{(1)}(\zeta)} \right] \sin n(\phi - \phi_0), \quad (34)$$

$$B_{\phi} = \sum_{n=0}^{\infty} \frac{\tau_n (-1)^n}{H_n^{(1)}(\zeta)} \left[-1 + \frac{\epsilon - \cos^2 \theta}{\sin \theta} \cdot \frac{k \tilde{\gamma}_{n\alpha} \tilde{r}_{n\beta} H_n^{(1)'}(\zeta)}{\tilde{\delta}_n H_n^{(1)}(\zeta)} - \frac{n^2 \cot^2 \theta}{\epsilon \zeta^2} (\epsilon - 1)(\epsilon - \cos^2 \theta) \frac{k^2 \tilde{\gamma}_{n\alpha} \tilde{\gamma}_{n\beta}}{\tilde{\delta}_n} \right] \cos n(\phi - \phi_0), \quad (35)$$

and $\tilde{f} = (f)_{u=k\cos\theta}$. In particular, observe that $S_{||\theta}$ and $S_{||\phi}$ are even and odd functions of $(\phi - \phi_0)$, respectively, as it must be by reason of symmetry. Also, $S_{||\phi} = 0$ when $\epsilon = 1$. If the cylindrical structure were absent, the dipole at the origin ($\rho_0 = z_0 = 0$) and axially oriented ($\hat{c} = \hat{z}$) would yield $S_{||\theta} = \sin \theta$, $S_{||\phi} = 0$, as expected.

4. Asymptotic Expansions for Thin Substrate

We limit our considerations to the far field produced by a dipole on the substrate and parallel to the z axis, in the equatorial plane $\theta = \frac{\pi}{2}$, so that $S_{\parallel\phi} = 0$. We assume

$$kb \gg 1, \quad |k_1 D| \ll 1; \quad (36)$$

the second inequality means that the coating layer is electrically thin. Then

$$\begin{aligned} Z_n(k_1 a) &\approx Z_n(k_1 b) - k_1 D Z'_n(k_1 b), \\ Z'_n(k_1 a) &\approx Z'_n(k_1 b) + k_1 D \left[1 - \frac{n^2}{(k_1 b)^2} \right] Z_n(k_1 b), \end{aligned} \quad (37)$$

where $Z_n = J_n$ or $H_n^{(1)}$; substitution into (32) yields, for $\theta = \pi/2$:

$$(S_{\parallel\theta})_{\theta=\frac{\pi}{2}} = S = -\frac{2ikD}{\pi kb} \sum_{n=0}^{\infty} \frac{\tau_n (-1)^n \cos n(\phi - \phi_0)}{H_n^{(1)}(kb) - kD H_n^{(1)'}(kb)}. \quad (38)$$

Set:

$$\phi = \phi - \phi_0 - \pi$$

$$\eta_0 = -ikD,$$

(39)

and observe that η_0 would be the relative surface impedance of a thin substrate with magnetic permeability equal to that of free space.

Then:

$$\begin{aligned}
S &= \frac{2\eta_0}{\pi kb} \sum_{n=-\infty}^{\infty} \frac{(-1)^n e^{-i \frac{\pi}{2} n} \cos n\theta}{H_n^{(1)}(kb) - i\eta_0 H_n^{(1)'}(kb)} \\
&= \frac{2i\eta_0}{\pi kb} \int_C \frac{e^{-i \frac{\pi}{2} v} \cos v\theta}{[H_v^{(1)}(kb) - i\eta_0 H_v^{(1)'}(kb)] \sin \pi v} dv \quad (40)
\end{aligned}$$

where the contour C is along the real axis and just above it in the complex v -plane, from $-\infty$ to $+\infty$. The integral in (40) is similar to the one studied by Gorainov [16] in relation to plane-wave scattering by a cylinder. Following [16], we set

$$e^{-i v \frac{\pi}{2}} = e^{i v \frac{3\pi}{2}} - 2ie^{i v \frac{\pi}{2}} \sin \pi v \quad (41)$$

in the integrand of Eq. (40), so that

$$S = S_1 + S_2$$

where

$$S_1 = \frac{4\eta_0}{\pi kb} \int_C \frac{e^{i v \frac{\pi}{2}} \cos v\theta}{M_v(kb)} dv, \quad (42)$$

$$S_2 = \frac{2i\eta_0}{\pi kb} \int_C \frac{e^{i v \frac{3\pi}{2}} \cos v\theta}{M_v(kb) \sin \pi v} dv, \quad (43)$$

with

$$M_v(kb) = H_v^{(1)}(kb) - i\eta_0 H_v^{(1)'}(kb). \quad (44)$$

The integral S_1 has a stationary point, as is seen by using Debye's expansion for $H_v^{(1)}$ in (44); the integral S_2 does not have a stationary point. Assume

$$|v - kb| > |v|^{1/3}, \quad (45)$$

then, in a region about the origin in the v -plane (for details see, e.g. [17,18]):

$$S_1 \sim \eta_0 \sqrt{\frac{2}{\pi kb}} \int_C dv \frac{4\sqrt{1 - (\frac{v}{kb})^2}}{1 - i\eta_0 \sqrt{(\frac{v}{kb})^2 - 1}} \cdot \left\{ \exp i \left[v \left(\frac{\pi}{2} + \phi + \arccos \frac{v}{kb} \right) - \sqrt{(kb)^2 - v^2} + \frac{\pi}{4} \right] + \exp i \left[v \left(\frac{\pi}{2} - \phi + \arccos \frac{v}{kb} \right) - \sqrt{(kb)^2 - v^2} + \frac{\pi}{4} \right] \right\}; \quad (46)$$

the first integral in (46) has a stationary point at $v_0 = -kb \sin \phi$, whereas the second integral has no stationary point. A stationary phase evaluation of S is therefore obtained by considering the stationary phase contribution due to the first term in the integrand of Eq. (46):

$$S \sim - \frac{2ikD \cos(\phi - \phi_0)}{1 - ikD \cos(\phi - \phi_0)} e^{-ikb \cos(\phi - \phi_0)}. \quad (47)$$

On the basis of Eq. (36) the denominator in (47) may be replaced by unity, so that

$$S \sim - 2ikD \cos(\phi - \phi_0) e^{-ikb \cos(\phi - \phi_0)}. \quad (48)$$

At the point of stationary phase, condition (45) is satisfied if

$$|\phi - \phi_0| < \frac{\pi}{2} - \sqrt{2} (kb)^{-4/3}, \quad (49)$$

which defines the region of free space into which direct radiation by the dipole occurs. Thus, Eq. (48) is valid in the "illuminated region" defined by (49), as shown in Fig. 3.

The far field in the penumbra and shadow regions, where inequality (49) does not hold, is obtained by letting

$$v = kb + mt, \quad m = \left(\frac{kb}{2}\right)^{1/3} \gg 1 \quad (50)$$

into Eq. (44), so that:

$$M_v(kb) = \frac{-1}{m\sqrt{\pi}} \left[w_1(t) + \frac{kD}{m} w_1'(t) \right], \quad (51)$$

where $w_1(t)$ is Airy's function in Fock's notation [18]. The poles of (40) in the complex v -plane are the zeros of $M_v(kb)$, i.e.:

$$\frac{w_1'(t_s)}{w_1(t_s)} = - \frac{m}{kD}. \quad (52)$$

Since this last ratio is large compared to unity,

$$t_s \approx t_{0s} - \frac{kD}{m}, \quad (53)$$

where the zeros t_{0s} ($s = 1, 2, \dots$) of $w_1(t_{0s}) = 0$ are well tabulated.

Since $\text{Im} v > 0$ at t_s , we may rewrite Eq. (40) as:

$$s = \frac{kD}{m} \left[f(\xi_+, \frac{kD}{m}) e^{ikb(\frac{\pi}{2} + \phi)} + f(\xi_-, \frac{kD}{m}) e^{ikb(\frac{\pi}{2} - \phi)} \right], \quad (54)$$

where

$$\xi_{\pm} = m(\frac{\pi}{2} \pm \phi), \quad (55)$$

and the generalized Fock function

$$f(\xi, \rho) = \frac{1}{\sqrt{\pi}} \int_{\Gamma} \frac{e^{i\xi t}}{w_1(t) + \rho w_1'(t)} dt \quad (56)$$

is well known, and can be evaluated e.g. by residues at the poles (53);

the contour Γ starts at infinity in the angular sector $\pi > \arg t > \pi/3$,

passes between $v = kb$ and the pole of the integrand nearest the origin (i.e. $t = t_1$), and ends at infinity in the angular sector $\pi/3 > \arg t > -\pi/3$ (see fig. 4).

The approximation (54) includes only the first two creeping waves, which complete less than one complete turn around the cylinder; the geometric interpretation of the two terms in Eq. (54) is shown in fig. 5.

5. Arrays of Longitudinal Dipoles

An axially oriented dipole at angular position ϕ_0 on the substrate produces the far-field pattern of Eq. (48) in the illuminated portion of its equatorial plane. Consider an array of n such dipoles with angular separation α between dipoles, i.e. the total array angle is $(n - 1)\alpha$ (see fig. 6). The far-field point of observation is in the illuminated region of all dipoles if

$$-\frac{\pi}{2} + (n - 1)\alpha + \sqrt{2}(kb)^{-4/3} < \phi < \frac{\pi}{2} - \sqrt{2}(kb)^{-4/3}. \quad (57)$$

Under limitation (57), dipoles fed with equal amplitude and progressive phase shift β yield the pattern:

$$S_{\text{total}} = 2kD \frac{\partial}{\partial(kb)} \sum_{l=0}^{n-1} e^{-ikb \cos(\phi - l\alpha) + il\beta}. \quad (58)$$

6. Concluding Remarks

The basic analysis for studying the behavior of printed circuit antennas on cylindrical structures has been presented herein. Numerical results pertaining to current distribution and other antenna characteristics for various substrate parameters will be presented.

References

- [1] I. J. Bahl and P. Bhartia (1980), Microstrip Antennas, Artech House, Dedham, MA.
- [2] IEEE Trans. Antennas Propag. (1981), special issue on microstrip antennas and arrays (D. C. Chang, editor), Vol. AP-29, No. 1.
- [3] K. R. Carver and J. W. Mink (1981), "Microstrip antenna technology", IEEE Trans. Antennas Propag., AP-29, 2 - 24.
- [4] R. J. Mailloux, J. F. McIlvenna and N. P. Kernweis (1981), "Microstrip array technology", IEEE Trans. Antennas Propag. AP-29, 25-37.
- [5] D. C. Chang and E. F. Kuester (1981), "Total and partial reflection from the end of a parallel-plate waveguide with an extended dielectric slab", Radio Science 16, 1 - 13.
- [6] D. C. Chang (1981), "Analytical theory of an unloaded rectangular microstrip patch", IEEE Trans. Antennas Propag., AP-29, 54-62.
- [7] E. F. Kuester and D. C. Chang (1981), "Resonance and Q properties of isosceles triangular patch antennas of 60° and 90° vertex", National Radio Science Meeting, Los Angeles, CA.
- [8] E. H. Newman and P. Tulyathan (1981), "Analysis of Microstrip antennas using moment methods", IEEE Trans. Antennas Propag., AP-29, 47-53.
- [9] I. E. Rana and N. G. Alexopoulos (1981), "Current distribution and input impedance of printed dipoles", IEEE Trans. Antennas Propag., AP-29, 99 - 105.

- [10] N. G. Alexopoulos and I. E. Rana (1981), "Mutual impedance computation between printed dipoles", IEEE Trans. Antennas Propag., AP-29, 106-111.
- [11] N. G. Alexopoulos and P. L. E. Uslenghi (1981), "Microstrip dipoles on spherical structures", National Radio Science Meeting, Los Angeles, CA.
- [12] C. -T. Tai (1971) Dyadic Green's Functions in Electromagnetic Theory, Intext, Scranton, PA.
- [13] C. -T. Tai (1973), "Eigen-function expansion of dyadic Green's functions", Math. Note 28, AFWL, Kirtland AFB, NM.
- [14] C. -T. Tai (1976), "Singular terms in the eigen-function expansion of dyadic Green's function of the electric type", Math. Note 65, AFWL, Kirtland AFB, NM.
- [15] R. E. Collin (1981), "Dyadic Green's functions-Current views on singular behavior", session on Scattering and Diffraction, 20th General Assembly of the International Union of Radio Science, Washington, D.C.
- [16] A. S. Goriainov (1958), "An asymptotic solution of the problem of diffraction of a plane electromagnetic wave by a conducting cylinder", Radiotekhnika i Elektronika 3, 23 - 39.
- [17] G. N. Watson (1966), A Treatise on the Theory of Bessel Functions, 2nd ed., Cambridge University Press, Cambridge, England.
- [18] J. J. Bowman, T.B.A. Senior and P.L. E. Uslenghi (1969), Electromagnetic and Acoustic Scattering by Simple Shapes, North-Holland, Amsterdam.




Figure 1 Geometry of the Problem




Figure 2 Path of Integration Along the Reu -axis




Figure 3 Geometric Interpretation of Condition (49)




Figure 4 Contour Γ and Poles in the Complex ν -plane





Figure 5 Geometric Interpretation of the Creeping-wave Terms in Equation (54); (a) $\xi = \xi_+$; (b) $\xi = \xi_-$




Figure 6 Geometry for Circumferential Array

